

SHORT OUTLET REDUCING TEE C X C X C


ASME BPE DT-4.1.2-9 (DT-20)

Hygienic Clamp Joint: Short Outlet Reducing Tee.



Technical information

Sizes	see table
Connections	Tri-clamp
Material	1.4404 (316L)
Finishes	Interior surf. SF1
Certificates (st.)	3.1 material
Certificates (opt.)	2.2 surface finish



Size	A	B	ØIDx	ØFx	ØIDy	ØFy
¾" x ¼"	57.2	57.2	7.75	25	4.57	25
½" x ¼"	60.3	60.3	9.4	25	4.57	25
½" x ¾"	60.3	60.3	9.4	25	7.75	25
¾" x ¼"	63.5	63.5	15.75	25	4.57	25
¾" x ¾"	63.5	63.5	15.75	25	7.75	25
¾" x ½"	63.5	63.5	15.75	25	9.4	25
1" x ¼"	66.7	66.7	22.1	50.5	4.57	25
1" x ¾"	66.7	66.7	22.1	50.5	7.75	25
1" x ½"	66.7	66.7	22.1	50.5	9.4	25
1" x ¾"	66.7	66.7	22.1	50.5	15.75	25
1½" x ½"	73.0	73.0	34.8	50.5	9.4	25
1½" x ¾"	73.0	73.0	34.8	50.5	15.75	25
1½" x 1"	73.0	73.0	34.8	50.5	22.1	50.5
2" x ½"	85.7	79.4	47.5	64	9.4	25
2" x ¾"	85.7	79.4	47.5	64	15.75	25
2" x 1"	85.7	79.4	47.5	64	22.1	50.5
2" x 1½"	85.7	79.4	47.5	64	34.8	50.5
2½" x ½"	92.1	85.7	60.2	77.5	9.4	25
2½" x ¾"	92.1	85.7	60.2	77.5	15.75	25
2½" x 1"	92.1	85.7	60.2	77.5	22.1	50.5
2½" x 1½"	92.1	85.7	60.2	77.5	34.8	50.5
2½" x 2"	92.1	85.7	60.2	77.5	47.5	64
3" x ½"	98.4	54.0	72.9	91	9.4	25
3" x ¾"	98.4	54.0	72.9	91	15.75	25
3" x 1"	98.4	54.0	72.9	91	22.1	50.5
3" x 1½"	98.4	54.0	72.9	91	34.8	50.5
3" x 2"	98.4	54.0	72.9	91	47.5	64
3" x 2½"	98.4	54.0	72.9	91	60.2	77.5
4" x ½"	120.7	104.8	97.4	119	9.4	25
4" x ¾"	120.7	104.8	97.4	119	15.75	25
4" x 1"	120.7	104.8	97.4	119	22.1	50.5
4" x 1½"	120.7	104.8	97.4	119	34.8	50.5
4" x 2"	120.7	111.1	97.4	119	47.5	64
4" x 2½"	120.7	111.1	97.4	119	60.2	77.5
4" x 3"	120.7	111.1	97.4	119	72.9	91
6" x 3"	181.0	136.5	146.7	167	72.9	91
6" x 4"	181.0	146.1	146.7	167	97.4	119

