TC imperial - BSPP Thread Male

Adapters are available as either male or female and are supplied with a BSPP thread. All threaded adapters are manufactured from solid 316L bar stock. This offers both excellent material properties and guarantees good controllable surface finishes. The flanged clamping side of the BSPP adapters is dimensioned and manufactured to 'mate up' directly with corresponding ferrules.


BSPP Male adapters are manufactured with parallel threads. All adapters are supplied with machined flats for wrench applications and to aid ease of assembly.



Mating

Technical information

Sizes	see table	
Connections	Tri-clamp	
Material	1.4404 (316L)	
Finishes	Interior surfaces SF1	
Certificates (st.)	3.1 material	
Certificates (opt.)	2.2 surface finish	



Clamp	Thread	Flange	Mating	L
Size	В	С	D	
1/2″	1⁄8″	25	10.0	30
	1⁄4″	25	10.0	30
	3⁄8″	25	10.0	30
	1/2″	25	10.0	32
	3⁄4″	25	10.0	35
3⁄4″	1⁄8″	25	16.0	30
	1⁄4″	25	16.0	30
	3⁄8″	25	16.0	30
	1/2″	25	16.0	32
	3⁄4″	25	16.0	35
1″	1/8″	50.5	22.0	30
	1⁄4″	50.5	22.0	30
	3/8″	50.5	22.0	30
	1/2″	50.5	22.0	35
	3/4″	50.5	22.0	35
	1″	50.5	22.0	35
1½″	1⁄8″	50.5	35.0	35
	1⁄4″	50.5	35.0	35
	3⁄8″	50.5	35.0	35
	1/2″	50.5	35.0	35
	3⁄4″	50.5	35.0	35
	1″	50.5	35.0	35
2″	1/2″	64	47.6	35
	3⁄4″	64	47.6	40
	1″	64	47.6	40
	1½″	64	47.6	40
	2″	64	47.6	40





These are standard items. We also deliver other sizes, according to ISO, DIN and SMS. For more and the latest information use the QR-code to go to the website.

Clamn

Thread

Flange

215

ROMYNOX | THE NETHERLANDS | T +31 (0)85 043 31 00 | E INFO@ROMYNOX.NL | W WWW.ROMYNOX.NL