


RIGID STEM DIAL THERMOMETERS

Type TXR, with stainless steel case according to EN 13190

STANDARD MODEL:

CASE	: bayonet lock, AISI304/1.4301, IP-65
STEM - BULB	: AISI321/1.4541, see page 8 - 11
WINDOW	: mineral glass 4 mm
DIAL	: aluminium, black figures on white
POINTER	: aluminium, black
CONNECTION	: see page 8 - 11
RANGES	: from -200 upto +800°C, see page 28 - 30

EXAMPLE:



TXR100XA

OVERLOAD	: up to 30% F.S. (but max. 800°C)
ACCURACY	: ±1% F.S. / class 1
MOVEMENT	: brass
OPTIONS	: see page 32
CONTACTS	: see page 33-37
PT-100	: see page 42
TRANSMITTER	: see page 42

TYPE	MODEL	CASE DIAMETER (Ø in mm)				
		63	80	100	160	250
A 1130		TXR063XA	TXR080XA	TXR100XA	TXR160XA	TXR250XA
E 1131		TXR063XE	TXR080XE	TXR100XE	TXR160XE	TXR250XE
T 1133-x (x=A,B,C or D)		TXR063XT-x	TXR080XT-x	TXR100XT-x	TXR160XT-x	TXR250XT-x
F 1138		TXR063XF	TXR080XF	TXR100XF	TXR160XF	TXR250XF
OPTION		EXTRA COSTS				
Lx	LIQUID FILLED CASE: GLYCERINE (in combination with electrical device: Ondina oil, (see page 43)	TXR063Lx	TXR080Lx	TXR100Lx	TXR160Lx	TXR250Lx