


TBL ClearGreenTM 60

Phthalate (DEHP-Free) Vinyl Tubing

Softer for More Flexibility
Superior Quality
Smaller Footprint



Phthalate (DEHP) Free Vinyl Tubing

Superior Biocompatibility

Excellent Flexibility

BPA Free

For several years TBL plastics has taken a leadership position being the first to introduce a full line of Phthalate (DEHP) free vinyl tubing. Our trusted ClearGreenTM line has been widely accepted for its purity in the life sciences and consumer-product markets. With other manufacturers reacting to the need for Phthalate free vinyl, TBL now offers our ClearGreenTM 60 which is compounded from the same ingredients as our well established original formulation with one difference. CleargreenTM 60 was designed to be softer for use in laboratory equipment and vacuum lines. It addresses the concerns of REACH compliance and meets USP Class VI testing.

Demand the original ClearGreenTM by name.

TBL

ClearGreenTM60

Phthalate (DEHP-Free) Vinyl Tubing

Applications

General Laboratory
Vacuum Pumps
Biopharmaceutical
Condensers
Incubators
Desiccators
Gas Lines
Drain Line

Quality Standards

USP Class VI
REACH Compliant
ROHS Compliant
Meets 3A Standards
BSE/TSE Compliant

Sterilization Methods

Gamma Stable
Ethylene Oxide
Autoclave

Stock Sizes

Part Number	ID	OD
CG-60-032X093	1/32"	3/32"
CG-60-063X125	1/16"	1/8"
CG-60-062X187	1/16"	3/16"
CG-60-093X156	3/32"	5/32"
CG-60-093X218	3/32"	7/32"
CG-60-125X187	1/8"	3/16"
CG-60-125X250	1/8"	1/4"
CG-60-156X281	5/32"	9/32"
CG-60-187X312	3/16"	5/16"
CG-60-187X375	3/16"	3/8"
CG-60-187X437	3/16"	7/16"
CG-60-187X562	3/16"	9/16"
CG-60-250X375	1/4"	3/8"
CG-60-250X500	1/4"	1/2"
CG-60-250X437	1/4"	7/16"
CG-60-250X625	1/4"	5/8"
CG-60-312X500	5/16"	1/2"
CG-60-312X562	5/16"	9/16"
CG-60-312X625	5/16"	5/8"
CG-60-375X500	3/8"	1/2"
CG-60-375X625	3/8"	5/8"
CG-60-375X875	3/8"	7/8"
CG-60-437X625	7/16"	5/8"
CG-60-437X687	7/16"	11/16"
CG-60-500X625	1/2"	5/8"
CG-60-500X750	1/2"	3/4"
CG-60-500X1125	1/2"	1-1/8"
CG-60-625X1375	5/8"	1-3/8"
CG-60-750X1000	3/4"	1"
CG-60-750X1500	3/4"	1-1/2"

Property	Value	Method
Specific Gravity	1.16	ASTM D792
Color	Clear	
Hardness	58 Shore A	ASTM D2240
Tensile Strength	1700 psi	ASTM D412
Ultimate Elongation %	420%	ASTM D412
Melt Temperature	320° F	
Brittle Temperature, Degrees	-127° F	ASTM D746
Water Absorption, 24 Hours @72° F	0.11% Wt. Gain	ASTM D570

Demand the original ClearGreenTM by name.

Custom sizes and packaging available.
Consult factory for details.